

# Navigator®

HILLYARD  
FLOOR CARE

Navigator utilizes the latest advancement in acrylic polymer technology to deliver a protective floor coating that offers excellent clarity and durability. Navigator provides excellent resistance to scuffing, scratching, and heel marking. Navigator's optimal solids content makes it extremely easy to apply resulting in even, clear protective layers of finish for your floor.

## Features & Benefits

- Holds up to the most severe traffic.
- Clarity - Will not discolor even after months of wear.
- Easy to clean.

## Directions

**PREPARATION:** Strip other finishes from the floor with Hillyard Devastator®, Super Strip, or Power-Strip following label directions. Use floor machine with black pad or brush (do not use abrasive pads on tile containing asbestos). Remove stripping solution with a wet vacuum. Heavy rinse with Hillyard Nutra-Rinse® mixed 4 oz. per gallon of water and pick up with the wet vacuum. Damp mop all flooring twice with clean, cool water. Allow the floor to dry.

**APPLICATION:** On newer floors, a sealer is not necessary. Apply a minimum of 5 coats of Navigator with a flat mop applicator, clean synthetic mop, or Hillyard Multi-Flo®. Allow each coat to dry a minimum 45 to 60 minutes before applying the next. If a sealer is not used and the floor is porous, apply a minimum of 6 coats of Navigator.

**NOTE:** Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60°F (16°C).

**MAINTENANCE:** Use a Hillyard Super Hil-Tone® treated dust mop daily to remove loose dirt and grit. Damp mop or autoscrub as scheduled with Hillyard Super Shine-All®, Top Clean®, or Arsenal® Heavy Duty Floor Cleaner. After the floor has been cleaned, gloss may be restored by spray buffing with Hillyard Hil-Glo®, or damp mop with Hillyard Restorer according to label directions. Scrub and recoat as scheduled with only 1-2 coats of Navigator.

**FLOOR PAD RECOMMENDATIONS:** Strip – black; Spray Buff – red followed by white; Scrub and Recoat – blue or green; Autoscrubbing – red.

**NOTICE:** Do not use an ammoniated cleaner for daily care. If the floor is extremely porous, seal with Hillyard Hil-Tex+® or Terrazine® before applying Navigator. If stains are a problem, seal with Strong Guard®. Keep container closed when not in use. Do not pour unused finish or seal back into the original container.

## Certifications, Registrations & Notes

Meets slip resistance using ASTM D2047 and Underwriters Laboratories, Inc's, Method 410.



## Safety

See material safety data sheet and product label for safety information, handling and proper use.

## HMIS

	Concentrate
Health	0
Flammability	0
Reactivity	0

## Technical Specifications

Color	Milky white
Scent	Non-Objectionable
Appearance	Milky white liquid
pH (concentrate)	8.00 - 9.00
Non-Volatile Matter	19.00 - 21.00%
Dilution Rate	RTU

## Availability

Item	Pack
HIL0053606	4 - 1 Gallon Containers
HIL0053607	1 - 5 Gallon Bag-In-Box
HIL0053609	1 - 55 Gallon Drum

**Coverage Rates:** 1,500 - 2,000 Sq. Ft. per Gallon  
*Rates can vary greatly based on surface and application method.*

HILLYARD

P.O. Box 909  
St. Joseph, MO 64502  
1-800-365-1555  
www.hillyard.com